

TSC Adjustable Slipping Torque Wrenches


Torque range from 1 to 10 N.m

Compact, versatile and lightweight tools which eliminate over-tightening in a wide range of industrial applications, including maintenance and repair. Calibrated scale allows for adjustment of torque. EPA compliant.

TSC 10



Slipping Mechanism
Incorrect tightening is impossible



Absolute accuracy and consistency. Accurate process control is ensured by eliminating under and over tightening, due to the unique Slipping Technology

Calibrated scale. A visible scale allows the user to adjust the tool to their desired torque setting, enabling a range of different torque settings to be applied

Ease of use. Can be used in restricted spaces through its compact slimline design

Electronics. Ideal for safe electronic component assembly and servicing, as this tool is EPA compliant for use in Electrostatically Sensitive Areas

Long tool life. High quality, durable design and construction, minimises replacement and downtime costs

Production efficiency. Improved operator comfort and productivity, from the ergonomic design, that includes lightweight materials and moulded plastic handgrip

Tool can be kept accurate and up to date with our Calibration service.

Versatility. Versatile tools ideal for Maintenance & Repair applications where a range of torques can be applied quickly and easily to a variety of fasteners and connectors

INDUSTRY SECTORS

Maintenance & Repair



Aerospace



Electronics

Manufacturing



Automotive



Consumer Products

For more information:

HUB Electronics Limited Telephone: **01403 255225** Email: sales@hubelectronics.co.uk Web: www.hubelectronics.co.uk

Order Code	Model	← Calibrated Range →		Drive	k	mm	g	Accuracy	ISO 6789 Class	
		Range	Scale							
056020	TSC 5	1-5 N.m	0.05 N.m	$\frac{1}{4}$	195	235	+/- 6%	2A	✓	
056040	TSC 10	2-10 N.m	0.1 N.m	$\frac{1}{4}$	195	235	+/- 6%	2A	✓	
056060	TSC 45	10-45 lbf.in	0.5 lbf.in	$\frac{1}{4}$	195	235	+/- 6%	2A	✓	
056080	TSC 90	20-90 lbf.in	1.0 lbf.in	$\frac{1}{4}$	195	235	+/- 6%	2A	✓	