


Data sheet | Item number: 222-412

Compact splicing connector; 2-conductor terminal block; with operating levers; max. continuous service temperature 85°C

[www.wago.com/222-412](http://www.wago.com/222-412)



Data  
Electrical data



Rated voltage (II / 2)	400 V
Rated impulse voltage (II / 2)	4 kV
Rated current	32 A
Legend (ratings)	(II / 2) $\triangleq$ Overvoltage category II / Pollution degree 2

### Connection data

Connection technology	CAGE CLAMP®
Actuation type	Operating lever
Connectable conductor materials	Copper Aluminum
Solid conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Stranded conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 4 mm <sup>2</sup> / 28 ... 12 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 Inch
Total number of connection points	2
Total number of potentials	1
Type of wiring	Side-entry wiring

### Geometrical Data

Width	12.4 mm / 0.488 Inch
Height	14.5 mm / 0.571 Inch
Depth	20.5 mm / 0.807 Inch

### Material Data

Color	gray
Flammability class per UL94	V2
Fire load	0.067 MJ
Weight	3.053 g


### Environmental Requirements

Ambient temperature (operation)	40 °C
Continuous operating temperature up to	85 °C



### Commercial data

Packaging type	BOX
Country of origin	DE
GTIN	4050821346470
Customs Tariff No.	85369010000



## Country specific Approvals

Logo	Approval	Certificate name
	ENEC 15 UL International Demko A/S	ENEC-01360

## Ship Approvals

Logo	Approval	Certificate name
	ABS American Bureau of Shipping	15-HG1419918-PDA
	LR Lloyds Register	04/20013 (E4)

## UL-Approvals

Logo	Approval	Certificate name
	UL UL International Germany GmbH	E69654
	UL Underwriters Laboratories Inc.	E201573

Subject to changes.

WAGO Kontakttechnik GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.