


Data sheet | Item number: 222-415

Compact splicing connector; 5-conductor terminal block; with operating levers; max. continuous service temperature 85°C



www.wago.com/222-415



Data

Electrical data

Rated voltage (II / 2)	400 V
Rated impulse voltage (II / 2)	4 kV
Rated current	32 A
Legend (ratings)	(II / 2) ≙ Overvoltage category II / Pollution degree 2



Connection data

Connection technology	CAGE CLAMP®
Actuation type	Operating lever
Connectable conductor materials	Copper Aluminum
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Stranded conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 4 mm ² / 28 ... 12 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 Inch
Total number of connection points	5
Total number of potentials	1
Type of wiring	Side-entry wiring

Geometrical Data

Width	26.6 mm / 1.047 Inch
Height	14.5 mm / 0.571 Inch
Depth	20.5 mm / 0.807 Inch

Material Data

Color	gray
Flammability class per UL94	V2
Fire load	0.13 MJ
Weight	6.581 g

Environmental Requirements

Ambient temperature (operation)	40 °C
Continuous operating temperature up to	85 °C



Commercial data

Packaging type	BOX
Country of origin	DE
GTIN	4044918464956
Customs Tariff No.	85369010000
Product Group	7 (Push Wire Conn.)



Country specific Approvals

Logo	Approval	Certificate name
	ENEC 15 UL International Demko A/S	ENEC-01360

Ship Approvals

Logo	Approval	Certificate name
	ABS American Bureau of Shipping	15-HG1419918-PDA
	LR Lloyds Register	04/20013 (E4)

UL-Approvals

Logo	Approval	Certificate name
	UL UL International Germany GmbH	E69654
	UL Underwriters Laboratories Inc.	E201573

Subject to changes.

WAGO Kontakttechnik GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.