



HEN.3M.322.XLNP

MECHANICAL DETAILS

Shell Style Model HE* : Fixed receptacle
nut fixing for printed circuit
watertight


Keying

Housing Material Environment friendly aluminium
(nickel plated, anthracite color)
shell and nut, other pieces
bronze/brass

Cable Fixing 0 - 0 mm

Variant 2 P : Watertight

			A	C	H	L	N
Mm.			23.0	22.8	10.16	20.8	16.8
In.			0.91	0.90	0.40	0.82	0.66



PERFORMANCE DETAIL

Insert 3M.322 : 22 Low Voltage

Insulator

Specifications

Contact Type: Print (straight)

Max. Matings: 5000

Contact Dia.: 0.7 mm (0.028in)

R (max): 6.1 mOhm



OTHER CHARACTERISTICS

Shell Style/Model Libellé

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz]

Shock Resistance: 100 g [6 ms]

Operating -20°C/ +80°C

Climatical 15/200/21 (Al. shell)

Lighting strike EIA 10K amps - 6 times

EMI Shielding EIA - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB

IP Rating 68