



FGS.0M.303.XLMT

MECHANICAL DETAILS

Shell Style Model FG* : Straight plug with arctic grip and mold stop


Keying 3 keys (beta=155, gamma=50, plug: female contacts, receptacle: male contacts)

Housing Material Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces bronze/brass

Cable Fixing 0 - 0 mm

Variant 2 :

				A	B	C	D	F
Mm.				14.4	8.8	12.7	8.0	10.7
In.				0.57	0.35	0.50	0.31	0.42



PERFORMANCE DETAIL

Insert 0M.303 : 3 Low Voltage

Insulator

Specifications

Contact Type: Crimp

Max. Matings: 5000

Contact 30 N

Contact Dia.: 0.9 mm (0.035in)

Bucket Dia.: 1.1 mm (0.043in)

Min. Conductor: 0.25 mm² (AWG 24)

Max. Conductor: 0.5 mm² (AWG 20)

R (max): 4.8 mOhm

Extractor: DCF.93.090.4LT

Positioner: DCE.91.090.3MM



OTHER CHARACTERISTICS

Shell Style/Model Libellé

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz]

Shock Resistance: 100 g [6 ms]

Operating -55°C / +200°C

Climatical 15/200/21 (Al. shell)

Lighting strike EIA 10K amps - 6 times

EMI Shielding EIA - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB

IP Rating 68

